

TOTAL GLAZE

888.702.9915
www.totalwall.com

100% Acrylic Protective Clear Coat For A Weatherproof Seal. **AMERICA'S EIFS AND STUCCO COMPANY!**

Total Glaze is a high solids 100% acrylic emulsion, which is used as a protective clear coat over a variety of surfaces including masonry, EIFS and wood.

Total Glaze can produce either a satin finish or rich glossy finish on surfaces depending on the number of coats applied and application technique used.

Total Glaze is designed for exterior wall surfaces and will remain clear even when exposed to direct sunlight.



Coverage

- Easy to use; brush, roller or spray
- Performs against all weather conditions
- Meets VOC, VOS requirements
- Low odor and low toxicity
- Non-yellowing, easy cleanup w/water

Porous substrates: 120-200 sq.ft. / gal./coat
Non-porous substrates: 200-250 sq.ft. / gal./coat

Two coats are recommended for weatherproofing.

Application:

Prepare surface by removing any dirt, oils, loose debris or any substance that may interfere with the bond. Allow the surface to dry. Previously sealed or treated surfaces should have a 4' x 4' test area coated with Total Glaze to test adhesion. It is advisable to fill any spalled or broken areas of substrate with a suitable patching material prior to application of the coating. Any cracks should be filled with a paintable grade acrylic caulk and allow to cure 4 hours before beginning coating.

Stir product for 30 seconds with a low speed mixer or manually stick-stir as desired. Do not beat excessive air into the product. Apply by roller, brush or airless sprayer.

When using a roller, the nap thickness can be varied to compensate for the substrate characteristics and the desired result. Thin product with up to 5 ounces of water per gallon if needed. For higher sheen or additional weatherproofing multiple coats are recommended

Handling and Storage

Do not apply to frozen or saturated surfaces. Do not apply if precipitation is forecast within 8 hours of application. Do not apply if the temperature cannot be maintained above 40F for 24 hours. Shelf life in closed containers is 18-24 months when stored at 50-100F. Keep containers sealed and under cover when not in use.

Maintenance

If an area that has been coated with Total Glaze becomes dirty or stained, clean with a mild cleaner solution and low-pressure spray rinse. For scars, broken or damaged areas, repairs should be made with the same products and then coated with Total Glaze.

Precautions

Total Glaze is an alkaline water based material. Do not ingest. Avoid contact with skin and eyes. In case of contact, flush with water. For contact with eyes, get immediate medical attention in addition to flushing. Wear safety glasses and protective clothing. Keep out of reach of children and pets.



888.702.9915 Phone

888.702.9916 Fax

www.totalwall.com

Technical Data

Flash point	>200 F Seta (non-flammable)
Density	8.5 lb./gal
Viscosity	Approx. 2000 CPS
pH	9.0 - 9.8
Chemistry	100% acrylic
Solvent System	Aqueous
Adhesion	Internal Wet Adhesion Promoters